



- ① 30-INCH LINEAR LENGTH WIRE, COILED
- ② WATERPROOF CONNECTION
- ③ ID TAG
- ④ VALVE BOX WITH COVER
- ⑤ FINISH GRADE/TOP OF MULCH
- ⑥ CONTROL VALVE: SUPERIOR 950PRS VALVE
- ⑦ PVC SCH 80 NIPPLE (CLOSE)
- ⑧ PVC SCH 40 ELL
- ⑨ PVC SCH 80 NIPPLE (AS REQD LENGTH)
- ⑩ BRICK (1 OF 4)
- ⑪ PVC MAINLINE PIPE
- ⑫ SCH 80 NIPPLE (2-INCH LENGTH, HIDDEN) AND SCH 40 ELL
- ⑬ PVC SCH 40 TEE OR ELL
- ⑭ PVC SCH 40 MALE ADAPTER
- ⑮ PVC LATERAL PIPE
- ⑯ 3-INCH MINIMUM DEPTH OF 3/4-INCH WASHED GRAVEL



Member of Stearns Manufacturing Group, Inc.

DATE: 03-07-2013	PART NO.	REV
DRWN BY: AES	950PRS SERIES	A
CHKD BY: DS	TITLE INSTALLATION, FORWARD, 950PRS	
APPVD BY: SC		
SCALE: N.T.S		